



## MAG SERIES



**SMOOTH  
PAN / TILT**



**EASY SETUP  
AND TAKEDOWN**



**ALUMINUM & ABS  
CONSTRUCTION**



**M-LOCK  
ATTACHMENT**



**MAGNETIC  
CONNECTION**



**USER MANUAL**

**EU-KJ86008K**

## MAG SERIES

The KJI M-Lok Adapter is designed to effortlessly integrate with your M-Lok handguard and provide magnetic attachment capabilities for the KJI Mag Series. Crafted from durable ABS material, this compact and versatile adapter transforms your firearm into a magnetic powerhouse.

The KJI M-Lok Adapter seamlessly attaches to your rifle's M-Lok handguard, creating a secure connection that enables quick and reliable magnetic attachment to the KJI Mag Series.

Built to withstand the demands of shooting in various environments, this adapter ensures longevity and resilience in the field.

### SPECIFICATIONS

Mount Type	3/8"-16 Threaded
Material	Aluminum 6061-T6 / ABS
Finish	Black
Dimensions Base (in/mm)	1.5 x 1.5 x 1.375 / 38 x 38 x 35
Dimensions Adapter (in/mm)	1 x 2.25 x 1.25 / 25 x 57 x 32
Weight (g/oz)	164 / 5.7
Torque Spec for M-Lok screws	1.7 N-m

### INCLUDES:

- Mag Series Base & M-Lok Handguard Adapter
- Hex key
- Manual

## DIAGRAM

1. Mag Series Mounting Base
2. Mag Series M-Lok Handguard Adapter
3. M-Lok Hardware (Included with Adapter Assembly)



## ATTACHING / MOUNTING BASE TO TRIPODS OR OTHER MOUNTING FIXTURES

To mount the Mag Series Mounting Base to the tripod, you simply need to screw the base portion of the support to the  $\frac{3}{8}$ "-16 mounting screw on the top of your tripod. Thread the base onto the mounting screw until it has a good hand tight fit.



## ATTACHING / MOUNTING HANDGUARD ADAPTER TO RIFLE

To mount the Mag Series M-Lok Handguard Adapter to your rifle, you first need to install the mounting hardware through the 2 holes in the handguard adapter.



Once the hardware is installed on the handguard adapter align and place the adapter over the M-Lok slot in the hardware and nest the adapter into the slot. The solid base of the adapter will lay directly on the handguard when placed properly over the slot. If the base is not laying flat on the handguard make sure that the tabs on the bottom of the adapter are fully inserted into the slot.



Using an allen wrench tighten the screws. The M-Lok nut will turn 90 degrees perpendicular to the slot. Tighten to 1.7 N-m (15 in/lbs).

Do not overtighten the M-Lok hardware. Doing so may damage your Mag Series Handguard Adapter.

## MAINTENANCE

- DO NOT apply any grease or oil anywhere on this tripod.
- Clean with a mild detergent and a soft cloth only.
- Avoid extreme heat and do not use close to a flame.

## STORAGE

When not using the KJI Mag Series Mounting System proper storage is recommended.

This includes:

- Removal of the Mag Series Mounting Base from the tripod or mounting device.

## WARNING

Before handling the tripod, read and understand the contents of the manual. Follow all standard safety precautions and procedures during use.

- Never leave a loaded firearm on the tripod without having positive physical control over the shooting system.
- Do not exceed the tripod's maximum load capacity.
- Ensure all accessories are fastened.
- Always remove camera, spotting scopes and other accessories during setup or transport.

## TROUBLESHOOTING

- GRIP KNOB FEELS GRITTY OR DOESN'T TURN SMOOTHLY.

1. Wipe the handguard adapter and mounting base cavity thoroughly with a rag and make sure that there is not any debris in the cavity or stuck in the outer surface of the handguard adapter.
2. If this does not fix the issue please visit [www.kjiprecision.com](http://www.kjiprecision.com).

## NOTES

---

---

---

---

---

---



Please visit [www.kjiprecision.com](http://www.kjiprecision.com) for warranty details and information.

[www.kjiprecision.com](http://www.kjiprecision.com)